

FARM TECHNOLOGY
CATALOG

CANAG

FARM TECHNOLOGY



PROLINER3

CONTINUOUS WRAPPER MODEL

(ROUND BALE) ●

THE QUICKEST AND SIMPLEST BALE EJECTOR SYSTEM ON THE MARKET, MAINTENANCE FREE.

ADVANTAGES

- ◆ Use 40% less plastic than an individual wrapper
- ◆ More standard characteristics than our competitors

FEATURES

- Continuous round bale wrapper from 4' to 5' length and from 4' to 5'6" diameter
- 3 aluminium stretchers 30" (NEW)
- 13 HP Honda engine with electric starter
- 18 amps alternator
- Raise and lower front axle hydraulically
- Bale compaction adjustable hydraulically by brake system on wheels
- Direct drive (hydraulic)
- Front wheel drive with traction tires
- Hydraulic tailgate
- Manual hydraulic control « joystick » type
- For freight: length 14'8" / width 8'6" / height 9'4"
- Machine goes from 9'6" working mode to 8'6" transportation mode quickly and easily
- Baked powder paint

LIGHTS AND SECURITY

- Working lights
- Road lights
- Safety light to indicate that the engine is running
- Advanced security protection for users
- Security guards
- Emergency stop on the machine or by remote

PERFORMANCE

- Wrapping performance of 120 bales per hour
- Bale counter
- Plastic wrap shortage detector
- Plastic wrap stops on the bale, « NOT » on the joint
- Hermetic and uniform wrapping made possible by our hydraulic brake system and the ability to double the wrapping automatically on the joints

REMOTE CONTROL OR « DIRECT »

- Steering by remote control or direct
- Start and stop the motor by remote control or direct
- Eject bales by remote control or direct
- Double the plastic wrapping by remote control
- Securely restart the automatic system by remote control

Remote Control Included



PROLINER 3

Working Dimension			Approx. Weight
Length	Width	Height	4 400 lb
18'	10'	9'4"	

ALLLINER

CONTINUOUS WRAPPER HYBRID MODEL

(ROUND AND SQUARE BALE) ■ ●

THE QUICKEST AND SIMPLEST BALE
EJECTOR SYSTEM ON THE MARKET,
MAINTENANCE FREE.

ADVANTAGES

- ◆ Quick wrapping
- ◆ Easy to transport
- ◆ Low maintenance cost
- ◆ Proven technology

FEATURES

- Continuous round bale wrapper from 4' to 5' length and from 4' to 5'6" diameter and square bale from 3' to 4' by 6' in length
- 4 aluminium stretchers 30"
- 13 HP Honda engine with electric starter
- 18 amps alternator
- Raise and lower front axle hydraulically
- Bale compaction adjustable hydraulically by brake system on wheels
- Direct drive (hydraulic)

- Front wheel drive with traction tires
- Hydraulic tailgate
- Manual hydraulic control «joystick» type
- For freight: length 15' / width 8'6" / height 9'8"
- Machine goes from 9'6" working mode to 8'6" transportation mode quickly and easily
- Baked powder paint

REMOTE CONTROL OR « DIRECT »

- Working lights
- Road lights
- Safety light to indicate that the engine is running
- Advanced security protection for users
- Security guards
- Emergency stop on the machine or by remote

PERFORMANCE

- Wrapping performance of 120 bales per hour
- Bale counter
- Plastic wrap shortage detector
- Plastic wrap stop on the bale « NOT » on the joint
- Hermetic and uniform wrapping made possible by our hydraulic brake system and the ability to double the wrapping automatically on the joint



Remote Control
Included



REMOTE CONTROL OR «DIRECT»

- Steering by remote control or direct
- Start and stop the motor by remote control or direct
- Eject bales by remote control or direct
- Double the plastic wrapping by remote control
- Securely restart the automatic system by remote control

ALLLINER

Working Dimension			Approx. Weight
Length	Width	Height	4 500 lb
20'	10'	9'8"	

TWISTER100

PT-TW-110-06

INDIVIDUAL WRAPPER MODEL

(ROUND BALE) ●

ADVANTAGES

- ◆ Quick wrapping
 - ◆ Easy to transport
 - ◆ Low maintenance cost
 - ◆ Proven technology
- Allows to be used in the field as well as on-site
Lightweight and compact



FEATURES

- Individual round bale wrapper from 4' to 5' diameter
- Manual hydraulic wrapping
- Hydraulic plastic cutting system
- 1 aluminium stretcher 30"
- Allows the bale to dropped close to the ground
- Bale counter and turn counter
- Manual hydraulic control « joystick » type
- Baked powder paint

TWISTER100

Option	Details
13 HP	Honda 13 HP hydraulic unit with electric starter - 13 HP power unit with electric starter - Motor with 18 amps alternator

TWISTER150

PT-TW-150-31

SELF-LOADING BALE WRAPPER

(ROUND BALE) ●

FULLY AUTOMATED SELF-LOADING MACHINE, ATTACHED TO THE TRACTOR. FULL AUTOMATION OF THE PROCESS IS PROVIDED BY AN ADVANCED CONTROL SYSTEM WHICH ALLOWS PRE-PROGRAMMING.

FEATURES

- Technological system 'front-back' allows for work in the same direction as the direction of the press work (along a field), ensures fast loading of bales, wrapping with foil during the drive until the next bale, high efficiency and coupling the bale wrappers machine with the round baler, ensuring simultaneous rolling and wrapping bale during one way
- Adjustable shaft in the positions in work and transport effectively allows for collecting bales and transporting the machine over access roads including public ones to the field
- Universal film dispenser allows the use of 0.5 and 0.75 m. wide films
- Aluminum, milled film dispenser rollers provide the initial film stretching and appropriate adhesion during the wrapping process
- Hydraulic film catcher-cutter works automatically after each bale wrapping process, provides a considerable acceleration of the wrapping process and its efficiency
- Bale elevator allows for putting bales on their bottom or rolling them on their side surface into the field and protects the wrapped bale from possible damage during unloading
- Wide tyres provide the opportunity to work on wetlands and peat fields Hydraulic wrapper drive
- Bale elevator
- Hydraulic foil catcher-cutter
- Electrical installation allowing to move on public roads
- Wide tyres 400 x 60 - 15,5
- Universal foil feeders (500 / 750)



- Wrapped bale diameter 3'9"- 4'9"
- Wrapped bale width (approx.) 4'1"
- Maximum wrapped bale weight (approx.) 2205 lb
- Bale wrapping time (approx.) 100 sec.

TWISTER150

Working Dimension			Approx. Weight
Length	Width	Height	2 998 lb
18'9"	10'4"	7'3"	

TWISTER210

3P-TW-210-00

INDIVIDUAL WRAPPER MODEL

(ROUND BALE) ●

DESIGNED FOR SMALL AND MEDIUM SIZE FARMS. THE TWISTER210 IS INSTALLED ON THE THREEPOINT LINKAGE OF THE TRACTOR.

FEATURES

- Solid frame made from bent and welded sections, makes the whole design stable and resistant to overloads
- Universal foil film dispenser using 0.50 and 0.75 m. wide films. The 0.75 m. wide bale wrapping film requires only 16 turns of the wrapping table and greatly reduces the wrapping time
- Aluminium milled foil film dispenser rollers ensure the initial foil stretching, tightness and proper adhesion during the wrapping process
- Bale counter indicates the current number of foil layers and informs about the end of wrapping process. Wrapping method of the loaded bale is that successive film layers overleap each other by 50%. It ensures that the green fodder will be properly stored and efficiently ensiled
- Tilting table allows discharging wrapped bales, protecting them from mechanical damage at the same time. After unlocking the latch, the tilt table is lifted by tractor's hydraulic lifting system and the bale rolls back
- Mounted type construction allows mounting wrapper on the tractor three-point linkage and bale wrapping at the storage areas with the use of a loader
- Specially designed rollers ensure proper bale wrapping, so that even shapeless bales rotate properly
- Durable, maintenance-free bearings ensures long and failure-free work
- Foil cutter (additional equipment) enables cutting off the foil during the rotation of the table after bale unloading
- Bale elevator (additional equipment) allows putting bales on their bottom (on the right or left side of the bale wrapper)



- Wrapped bale diameter (approx.) 4'3"
- Wrapped bale width (approx.) 4'1"
- Maximum wrapped bale weight (approx.) 2205 lb
- Bale wrapping time (approx.) 120 sec.

TWISTER210

Working Dimension			Approx. Weight
Length	Width	Height	1 058 lb
8'5"	3'9"	3'9"	

TWISTER250

3P-TW-250-10

INDIVIDUAL
WRAPPER MODEL
(ROUND BALE) ●

THE TWISTER250 IS EQUIPPED WITH A LIFT ARM THAT PICKS THE ROLLEDUP BALES THAT ELIMINATING THE NEED OF ANY INTERVENTIONS EXCEPT FOR HE INSTALLATION OF NEW FILM ROLLS.

FEATURES

- Solid frame made from bent and welded sections, makes the whole design stable and resistant to overloads
- Universal foil film dispenser 0.50 and 0.75 m. wide films. The 0.75 m. wide bale wrapping film requires only 16 turns of the wrapping table and greatly reduces the wrapping time
- Aluminium milled foil film dispenser rollers ensure the initial foil stretching, tightness and proper adhesion during the wrapping process
- Bale counter indicates the current number of foil layers and informs about the end of wrapping process
- Wrapping method of the loaded bale is that successive film layers overleap each other by 50%. It ensures that the green fodder will be properly stored and efficiently ensiled
- Mounted type construction allows mounting wrapper on the tractor three-point linkage enables high mobility of the wrapper and low labor consumption due to oneperson operation
- Wheels rotating around their vertical axis combined with mounting of the machine on the three point linkage, provide high maneuverability of the tractor-wrapper set
- Drawbar (additional equipment) enables aggregatingthe bale wrapper by the tractor's transport fastener



- Foil catcher (additional equipment) enables catching and cutting foil in difficult weather conditions
- Hydraulic table lock (additional equipment) prevents the table from rotating on unevenness
- Wrapped bale diameter (approx.) 3'9" - 4'3"
- Wrapped bale width (approx.) 4'3"
- Maximum wrapped bale weight (approx.) 2205 lb
- Bale wrapping time (approx.) 120 sec.

TWISTER250

Working Dimension			Approx. Weight
Length	Width	Height	
7'	6'4"	7'	1 720 lb

SPREADER610

3P-SP-610-00

SPREADER

THE TWO DISC DISTRIBUTORS ARE INTENDED FOR SURFACE DISTRIBUTION OF MINERAL AND CRYSTALLINE FERTILIZERS OVER FARMLANDS FOR BASIC FERTILISING AND PLANTS NOURISHING.

FEATURES

- Mounted on a three-point hydraulic lift system
Robust frame construction optimally adjusted to the load capacity, guarantees long-term and reliable operation of the distributors
- Spreading system ensures even fertiliser dosing on the spreading discs and spreads fertiliser with precision on the field surface
- LIMES border spreading system (additional equipment) allows to work at the field boundaries in accordance with the fertilization regulations, while ensuring the delivery of the correct dose of fertilizer to the very border of the field. It also eliminates economic losses resulting from over-fertilization or from spreading fertilizer to adjacent fields
- Spreading discs feature two pairs of vanes, which allow spreading fertilizers at the operating width of 10 - 24 m.
- Border spreading discs (additional equipment) allow spreading of fertilizer at the edge of the field
- Hydraulically operated valves allow each dosing opening to be closed independently Flexible pendulum agitator ensures uniform feeding of fertilizers on the spreading discs
- Sieves installed in the tank protect the spreading zone of distributor against lumpy or dry fertilizer and impurities
- Foldable tarpaulin cover (additional equipment) installed on the container allows operating in various atmospheric conditions
- Hydraulic control
- Capacity 600 l
- Maximum load capacity 2 910 lb
- Working width depending on the use of vanes 32'8"-59' m.
- Spreading disc diameter 1'4"
- 2 spreading discs
- 2 vanes on disc
- Maximum working speed 12 km/h
- Maximum transport speed 25 km/h



SPREADER610

Working Dimension			Approx. Weight
Length	Width	Height	650 lb
4'	6'7"	4'	

SHREDDER1200

PT-BS-1200-00

BALE SHREDDER

(ROUND BALE) ●

ARE DESIGNED FOR SHREDDING,
FEEDING OR SPREADING OF
HAY, STRAW AND HAY SILAGE IN
STABLES OR OPEN AREAS.

FEATURES

- Designed to shred round bale
Control over the processing from the tractor driver's seat
Hydraulically controlled ejector channel allows for diverting the shredded material directly to the mangers and adjusting the ejection up to 14 m. (when spreading straw). The shredder allows control of the ejection channel direction in the range of 200°
- Knife drum shreds the fed material and feeds it to the discharge rotor shoulder blades, ensuring high discharge and efficiency of the machine. The bale shredder is equipped with two shredding barrels
- Grate mounted above the knife drum ensures an even source of material on the knife drum, protects the machine against clogging and increases its value and reliability
- Mechanical, chain floor conveyor thanks to the hydraulic drive, it can operate with a variable, steplessly adjustable speed
- Back loading wall activated by a hydraulic acuator allows for easy and quick loading of the bale onto the machine
- Oil flow regulator in the hydraulic distributor allows for controlling the speed of the bottom-mounted conveyor, which slides the material on the shredding drum.
- This enables adapting the linear speed of the conveyor to the type of shredded material and ensures optimal use of the machine's utilization capabilities

- Maximum straw spreading range 45'9"
- Maximum fodder feeding height 3'9"
- Maximum width of shredded bales 3'9"
- Maximum diameter of shredded bales 4'9"
- Number of simultaneously shredded bales 1 pc



SHREDDER1200

Working Dimension			Approx. Weight
Length	Width	Height	2 646 lb
11'2"	6'6"	6'	

SHREDDER1500

PT-BS-1500-00

BALE SHREDDER

(ROUND AND SQUARE BALE) ■ ●

ARE DESIGNED FOR SHREDDING,
FEEDING OR SPREADING OF
HAY, STRAW AND HAY SILAGE IN
STABLES OR OPEN AREAS.

FEATURES

- Multi-purpose design of the shredder allows feeding of the hay silage or spreading of straw in stables or open areas. Designed to shred both round and square bales.
- Allows for full control over the processing from the tractor driver's seat.
- Allows control of the ejection channel direction in the range of 200°.
- Equipped with two shredding barrels
- Grate mounted above the knife drum ensures an even source of material on the knife drum, protects the machine against clogging and increases its value and reliability.
- Mechanical, chain floor conveyor thanks to the hydraulic drive, it can operate with a variable, steplessly adjustable speed.
- Back loading wall activated by a hydraulic acuator allows for easy and quick loading of the bale onto the machine.
- Oil flow regulator in the hydraulic distributor allows for controlling the speed of the bottom-mounted conveyor, which slides the material on the shredding drum. This enables adapting the linear speed of the conveyor to the type of shredded material and ensures optimal use of the machine's utilization capabilities.
- Maximum straw spreading range 49'2"
- Maximum fodder feeding height 8'2"
- Maximum width of shredded bales 4'9"
- Maximum diameter of shredded bales 5'9"
- Number of simultaneously shredded bales 2 pc



SHREDDER1500

Working Dimension			Approx. Weight
Length	Width	Height	4630 lb
16'3"	7'8"	9'2"	

TRAILER-SL1000

PT-RBSL-1000-00

SELF-LOADING STACKING TRAILER

THE TRAILER SLIPS ITS SIDE FORK UNDER A BALE AND PICKS IT UP FROM THE GROUND. THE BALE IS THEN MOVED BY SPECIAL ARMS TOWARDS THE REAR PART OF THE BODY IN ORDER TO MAKE SPACE FOR NEXT BALES.

FEATURES

- Load body design enables the trailer to collect and transport bales (up to 8 bales with the diameter of 1.2 - 1.5 m.), crops and other materials (e.g. sand)
- Hydraulic distributor enables control from the cabin and ensures large comfort of work and high efficiency
- Support foot increases the stability of the trailer during the loading of heavy green fodder bales and also improves the safety of work
- Pneumatic brakes on all wheels and hand brake guarantee high safety of work
- Road lights allow the machine to be used on public roads without incurring additional costs
- Tandem chassis (rigid axles) and reinforced structure increase durability and resistance providing a load capacity of 6.5 t.
- Hydraulic acuator ensures bale unloading to the side, sliding backwards and vertical stacking, enabling adaptation to the different needs of users



- Capacity 6,5 t.
- Maximum bales number 8 pcs
- Maximum bales weight 1 764 lb
- Backward dumping angle 90°
- Side dumping angle 45°
- Maximum speed 25 km/h



TRAILER-SL1000

Working Dimension			Approx. Weight
Length	Width	Height	
21'1"	8'6"	10'5"	5 754 lb



1 866.677.8902

canag.co



300 boulevard Industriel
Saint-Germain-de-Grantham,
Québec (CANADA), J0C 1K0